

ITEM LIST



SURFACE



DECKING

Treated timber decking

28 x 145 mm, Lengths: 4 200 mm, Code: TD30-4200

	Qty.	\$ / uom	430.92 £
	27 pcs 113.40 m	3.80 £ / m	430.92 £

STRUCTURE



JOIST

carassing 47 x 150 mm

150 x 47 mm, Lengths: 4 200 mm, Code: TIM.FRAM.150.47-4200

	Qty.	\$ / uom	265.99 £
	10 pcs 42 m	4.52 £ / m	189.84 £




BEARER

carassing 47 x 150 mm

150 x 47 mm, Lengths: 4 200 mm, Code: TIM.FRAM.150.47-4200

	3 pcs 12.60 m	4.52 £ / m	56.95 £
--	---------------	------------	---------



BRACKET

Universal joist hanger for 100 mm and 150 mm joists

Code: JHJ

	16 pcs	1.20 £ / pcs	19.20 £
--	--------	--------------	---------

SURFACE FIXINGS




SCREWS

timber decking screw 50 mm for timber joists

Code: ds22

	Qty.	\$ / uom	19.80 £
	432 pcs 3 Box	6.60 £ / Box	19.80 £

VENTILATION



WEEDMATS

Ground cover weed control

Code: fabb

	Qty.	\$ / uom	16.64 £
	2 pcs	8.32 £ / pcs	16.64 £

SUPPORTS



POSTS

half bag of post mix


Code: PM0.5

	Qty.	\$ / uom	85.80 £
	12 pcs 6 Box	6.00 £ / Box	36.00 £

ITEM LIST



SUPPORTS



POSTS

1.2 x 75 x 75 (2 ex 2.4) post
75 x 75 x 2.400 mm, Code: TIM.75.75

12 pcs

Qty.

6 Box

\$ / uom

6.30 £ / Box

85.80 £

37.80 £



FIXINGS

coach screws 100 mm for fixing the drop beam to the post
Code: CS100MM

24 pcs

0.50 £ / pcs

12.00 £

SERVICES AND DOCUMENTS



INSTALLATION GUIDES

All project plans, cutting lists and instructions to use the above goods to create your chosen deck.

Code: PLAN

Qty.

1 pcs

\$ / uom

0.00 £ / pcs

0.00 £

0.00 £

Subtotal

819.15 £

20% GST

163.83 £

Grand total (incl. GST)

982.98 £

DESIGN LAYOUT




This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Treated timber decking (TD30-4200)

Area: 16 m², Perimeter: 16.00 m

Joist centers: 59 cm




STRUCTURE DESIGN LAYOUT



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

- Joist: carcassing 47 x 150 mm (TIM.FRAME.150.47)
Joist centers: 59 cm, span: max. 2,300 mm, cantilever: max. 200 mm
- Beam: carcassing 47 x 150 mm (TIM.FRAME.150.47)
span: max. 1,600 mm, cantilever: max. 200 mm
Anchored installation: Yes




STRUCTURE JOIST LAYOUT



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Joist: carcassing 47 x 150 mm (TIM.FRAM.150.47)
Joist centers: 59 cm, span: max. 2,300 mm, cantilever: max. 200 mm
Anchored installation: Yes




STRUCTURE SUPPORT LAYOUT



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Beam: carcassing 47 x 150 mm (TIM.FRAM.150.47)
span: max. 1,600 mm, cantilever: max. 200 mm
Anchored installation: Yes




STRUCTURE SUPPORT LAYOUT



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Beam: carcassing 47 x 150 mm (TIM.FRAM.150.47)
span: max. 1,600 mm, cantilever: max. 200 mm
Anchored installation: Yes




CUTTING LIST SURFACE PRODUCTS



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Area A


Pieces	Length	Cut	Pieces	Length	Cut
27 pcs.	/ 420 cm	400 			

CUTTING LIST JOISTS



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Area A


Pieces	Length	Cut	Pieces	Length	Cut
6 pcs.	J. / 420 cm	400 			

CUTTING LIST BEARER



This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Area A


Pieces	Length	Cut	Pieces	Length	Cut
3 pcs.	B. / 420 cm	400 			


CUTTING LIST PERIMETER




This information is for calculation purpose only. Before starting installation, check all dimensions. Refer to installation instructions, site conditions and governing regulations.

Area A

Pieces	Length	Cut	Pieces	Length	Cut
4 pcs.	P. / 420 cm	400 			



Laying Timber Decking Boards



Screw the decking boards into position using a golf tee or 100mm screw to produce a 5mm gap (X) between the boards. Sometimes the boards can be different widths at the ends; this is not bad machining of the timber, it is due to the timber treatment drying out at different rates.

If this is the case, centralise the boards and fix. Any boards that are not dead straight, fix at one end, kick over and fix. Keep the screws straight and fix in the last groove each side of the decking board at every joist. This ensures the screw tops are even throughout the decking.

TECHNICAL INFORMATION



POSTCRETE

Ready-to-use Blue Circle Postcrete Product Data Sheet

A ready-to-use blend of selected sand, cement and additives formulated for fixing wooden, concrete and metal posts.

USES



To fix all types of wood, metal and concrete posts.

DESCRIPTION

Blue Circle Postcrete is ready to use. No mixing is required.

PACKAGING

Blue Circle Postcrete is packed in weatherproof 20 kg plastic packaging.



SITWORK

For the best results follow these instructions:

1. Dig a hole relevant to post size - three times wider than the post and as deep as $\frac{1}{3}$ of fence heights above the ground.
2. Fill the hole with water to a third of the depth.
3. Pour in Blue Circle Postcrete evenly around post until no standing water is visible (powder completely covers water surface). Sprinkle water on top of powder.
4. Position and level post as required. Setting will take place in 5 to 10 minutes.
5. When set, cover top of hole with soil or grass.
6. You can fix fence panel right after the initial 10 minutes of post setting time.

Do not mix Blue Circle Postcrete with water by hand or machine. Please consult with the table on the reverse for guidance on the quantity of Blue Circle Postcrete to use or alternatively go to www.tarmac-bluecircle.co.uk/product/postcrete-trade/

STORAGE

Blue Circle Postcrete is a cement-based material and should be handled and stored with care. This product may be stored, unopened in either indoor or outdoor conditions. Information on the maximum storage period can be found on the bag.

CLEANING

All equipment should be cleaned with water. Do not flush down drains.

AVAILABILITY

Blue Circle Postcrete is available throughout the United Kingdom. Blue Circle Postcrete is supplied in 20 kg plastic bags.

CONDITIONS OF USE

- Blue Circle Postcrete may be used for the purposes of fixing domestic posts
- Blue Circle Postcrete may be used for fixing decking posts, rotary washing lines and small/medium sized gateposts (less than 1.0m width gate)
- Blue Circle Postcrete may not be used for general concreting, screeds, mortar, grout or render
- If a specified compressive strength is required, Blue Circle Postcrete should not be used
- Normal site practice to the relevant British and European Standards should always apply. Tarmac Cement cannot be held responsible where workmanship has not been carried out in accordance with good practice
- Manual handling should comply with *The Manual Handling Operations Regulations 1992*.

TECHNICAL SUPPORT

Further information and advice on this product and the full range of Tarmac Cement products can be obtained through the contacts listed below.

HEALTH AND SAFETY

Contact between cement powder and body fluids (eg, sweat and eye fluids) may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheets.

Post size	Hole size (width x depth)	Number of bags required
Round 5cm (2")	15cm (6") x 30cm (12")	1/4 bag
	15cm (6") x 45cm (18")	1/3 bag
	15cm (6") x 60cm (24")	1/2 bag
	20cm (8") x 30cm (12")	1/2 bag
	20cm (8") x 45cm (18")	3/4 bag
Square 7.5cm (3")	20cm (8") x 60cm (24")	1 bag
	15cm (6") x 45cm (18")	1/3 bag
	15cm (6") x 60cm (24")	1/2 bag
	15cm (6") x 75cm (30")	3/4 bag
	20cm (8") x 45cm (18")	3/4 bag
	20cm (8") x 60cm (24")	3/4 bag
	20cm (8") x 75cm (30")	1 bag
	25cm (10") x 45cm (18")	1 1/3 bags
	25cm (10") x 60cm (24")	1 1/2 bags
	25cm (10") x 75cm (30")	1 2/3 bags
	30cm (12") x 45cm (18")	2 bags
Square 10cm (4")	30cm (12") x 60cm (24")	2 bags
	30cm (12") x 75cm (30")	2 3/4 bags
	20cm (8") x 45cm (18")	2/3 bag
	20cm (8") x 60cm (24")	3/4 bag
	20cm (8") x 75cm (30")	1 bag
	25cm (10") x 45cm (18")	1 1/4 bags
	25cm (10") x 60cm (24")	1 1/3 bags
	25cm (10") x 75cm (30")	1 2/3 bags
	30cm (12") x 45cm (18")	1 3/4 bags
	30cm (12") x 60cm (24")	2 bags
30cm (12") x 75cm (30")	2 1/2 bags	

For further information

Technical helpdesk

Tel: 0845 812 6232

E-mail info-cement@tarmac.com

Customer services & sales

Tel: 0845 812 6300

E-mail customerservice@tarmac.com

Tarmac' and the 'circle logo' are registered trademarks. ©2015 Tarmac Trading Limited

The information in this data sheet is accurate at the time of printing, but Tarmac reserves the right to amend details as part of its product development programme. The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.